



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ :

G11B 7/135

A1

(11) International Publication Number:

WO 00/08641

(43) International Publication Date:

17 February 2000 (17.02.00)

(21) International Application Number: PCT/EP99/05518

(22) International Filing Date: 29 July 1999 (29.07.99)

(30) Priority Data:

98202673.4


7 August 1998 (07.08.98)

EP

(71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V.
[NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven
(NL).(72) Inventor: HENDRIKS, Bernardus, H., W.; Prof. Holstlaan 6,
NL-5656 AA Eindhoven (NL).(74) Agent: COBBEN, Louis, M., H.; Internationaal Octrooibureau
B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).(81) Designated States: JP, KR, European patent (AT, BE, CH, CY,
DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT,
SE).

Published

With international search report.

(54) Title: OPTICAL SCANNING DEVICE AND OPTICAL APPARATUS FOR READING AND/OR WRITING INFORMATION IN
AN INFORMATION PLANE PROVIDED WITH SUCH A DEVICE

(57) Abstract

An optical device for optically scanning an information plane (3) is described, which device comprises a radiation source (6) for supplying a scanning beam (17), and an objective system (10) for focusing the scanning beam to a scanning spot (18) on the information plane. The temperature dependence of the objective system can be compensated by a compensator which is arranged between the radiation source and the objective system and comprises a planoconvex first element (41) and a planoconcave second element (42), the convex surface of the first element being arranged against the concave surface of the second element, and the refractive indices of the first and the second element being equal at the design temperature but having a different temperature dependence.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

Optical scanning device and optical apparatus for reading and/or writing information in an information plane provided with such a device

Description

The invention relates to an optical device for optically scanning an information plane, comprising a radiation source for supplying a scanning beam, and an objective system for focusing the scanning beam to a scanning spot on the information plane.

The invention also relates to an apparatus for reading and/or writing an optical record carrier provided with such a scanning device.

The information plane may be the plane of an optical record carrier in the form of a disc or a tape in which the optically readable information is present or may be stored. Such a record carrier is, for example, the known compact disc (CD) for audio or CD-ROM for data or a record carrier derived therefrom, such as the DVD. The information plane may also be the surface of another object which can be examined, for example, with a scanning microscope.

Notably for optical record carriers, there is an increasing need of a scanning device with which increasingly smaller details can still be read distinctly because one wants to store an increasing quantity of information on the record carrier. The quantity of information which can be stored on an optical record carrier depends, inter alia, on the size of the scanning spot which is formed by the scanning device on the information plane of the record carrier. As the scanning spot is smaller, the information density may be larger.

The size of the scanning spot may be reduced by increasing the numerical aperture (NA) of the beam with which the scanning spot is formed.

An attractive possibility of increasing the NA without the costs for the objective system becoming too high, and the image field becoming too small, and without causing the problems due to the dispersion of the material from which the lens is formed, is to arrange a planoconvex lens between the actual objective lens and the record carrier. This planoconvex lens, also referred to as solid immersion lens or slider lens, may be situated at a very small distance from the record carrier, but also at a slightly larger distance, for example, 300 μm . The converging function of the objective system is then distributed across the actual objective lens and the planoconvex lens. An advantage of the use of the

planoconvex lens is that this lens introduces hardly any aberrations in the radiation beam.

A scanning device provided with such a planoconvex lens is known from
5 EP-A 0 727 777. This device comprises an optical scanning head with an objective lens and a planoconvex lens which converge a radiation beam to a numerical aperture of 0.84 for scanning a record carrier. The planoconvex lens may be arranged in a slider which is in sliding contact with the record carrier or floats on an aircushion.

The objective system is sensitive to changes of the refractive index or the
10 temperature. The tolerances for these changes may be alleviated by using separate drivers (actuators) for the objective lens in the planoconvex lens so that these elements cannot only be moved with respect to the record carrier but also with respect to each other. The separate drivers complicate the scanning device, render it more sensitive to disturbances and make it more expensive, which are great disadvantages, particularly for consumer uses. It is
15 therefore preferred to use a rigid objective system, i.e. a system in which the objective lens and the planoconvex lens are fixed with respect to each other. The elements of the objective system are preferably glass-replica lenses or completely synthetic material lenses. A replica lens is a lens consisting of a basic shape of glass on one or two refracting surface(s) on which a layer of transparent synthetic material is provided. The surface of the synthetic
20 material layer may easily be given an aspherical shape by means of a mold and a replica technique. The glass basic shape with the layer of synthetic material, which is in a sufficiently weak state, is pressed against a mold which comprises the negative of the desired shape and is subsequently cured. Also a lens element which consists completely of a synthetic material can easily be given one or two aspherical surface(s), for example, by
25 means of molding.

However, a glass-replica lens has the drawback that the refractive index changes due to temperature fluctuations in the desired wide temperature range of, for example -5°C to $+50^{\circ}\text{C}$ are too large so that the required quality of the scanning spot can no longer be achieved.

30 It is an object of the invention to provide a scanning device of the type described in the opening paragraph, comprising a rigid objective system in which the influence of temperature changes on the optical behavior is substantially eliminated. To this

end, the device according to the invention is characterized in that a temperature compensator comprising a cemented doublet of a planoconvex first element and a planoconcave second element is arranged between the radiation source and the objective system, the convex surface of the first element being arranged against the concave surface of the second element, and the refractive indices of the first and the second element being substantially equal at the design temperature but having a different temperature dependence.

The invention is based on the recognition that the temperature dependence of the objective system can be compensated by arranging an extra element, the temperature compensator, in the path of the radiation beam, which compensator does not have any optical strength at that temperature for which the refractive indices of the system have the starting values on which the design of the system was based, referred to as the design temperature in this description, but acquires such an optical strength at a change of the temperature that the spherical aberration produced at said temperature change in the objective system can be compensated. Since the compensator consisting of two elements has a flat entrance and exit surface and the refractive indices of these elements are equal at the design temperature, this compensator has no optical strength at the design temperature. Since the interface between the two elements in the compensator has a curvature and these elements have a different temperature dependence dn/dT , the compensator acquires an optical strength at a temperature which is different from the design temperature.

For example, if the objective system is designed for focusing a parallel radiation beam on the information plane of the record carrier, the beam entering the compensator will be a parallel beam and, at the design temperature, the beam exiting from the compensator will also be a parallel beam. At a different temperature, however, the beam exiting from the compensator will be slightly diverging or converging, dependent on the change in the objective system caused at that temperature.

It is to be noted that US-A 4,753,524 describes a lens system for reading a disc-shaped optical record carrier which consists of a cemented doublet on the object side and a single lens element or a combination of a positive and a negative lens element on the image side. Conditions are given for the Abbe factors of the lens elements and for the temperature dependence of the refractive indices of these elements in order that the lens system is independent of wavelength and temperature. As regards the temperature compensation, it is stated that the change, occurring at a temperature change, of the radii of curvature of the lens surfaces is compensated by a change of the axial thickness of the lens elements. It is further stated that the lens holder may undergo a considerable change at a

temperature change so that the position of the focus changes, and that a choice has been made to change the refractive indices at an increasing temperature in such a way that there is an intensified change in the position of the focus. The refractive indices of the elements of the doublet are, however, different and the doublet has at least one, and in most
5 embodiments two, curved outer surfaces. This doublet does not satisfy the condition that it should not have an optical strength at the design temperature.

Both elements of the compensator according to the invention may consist of a synthetic material, with the material for one element being of course different than that for the other element. These synthetic materials should then satisfy two criteria: maximally
10 equal refractive indices at the design temperature and a different temperature dependence of the refractive indices.

A preferred embodiment of the device is, however, further characterized in that one of the elements of the compensator consists of glass and the other element consists of a transparent synthetic material.

15 Since the refractive index of glass has a negligible temperature dependence, only the criterion that the refractive index of the synthetic material must be maximally equal to that of glass should be observed.

If intended for use in combination with a radiation beam having a wavelength of 650 nm, this preferred embodiment is further characterized in that the glass is
20 BAK4 and said synthetic material is Diacryl.

At said wavelength, the refractive index of the glass is then 1.566 and that of the synthetic material is 1.565, i.e. substantially equal to that of the glass.

The measure according to the invention is usable for various optical devices but may be particularly used to great advantage in a scanning device which is further
25 characterized in that the objective system comprises an objective lens and a planoconvex lens, the objective lens being situated on the object side and the planoconvex lens being situated on the image side, the convex surface of the planoconvex lens facing the objective lens.

As already noted, a large numerical aperture can be realized in a
30 relatively simple manner with such an objective system. Particularly for optical devices having a large numerical aperture, for which strict requirements are imposed on the optical quality of the elements of the device and of the device as a whole, the measure according to the invention fulfills a great need.

The objective system of the scanning device may also be sensitive to

wavelength changes because the material of the elements of this system has different refractive indices for different wavelengths; in other words, it shows dispersion. Particularly in a scanning device with which information must be both written and read and in which the intensity of the radiation source, in the form of a diode laser, must be switched between a reading level and a considerably higher writing level, this may yield problems because an offset of several nms of the emitted wavelength may occur when switching the diode laser. Due to the dispersion of the materials of the objective system, the focus of the radiation beam may get beyond the information plane of the record carrier at such a wavelength offset.

5 An embodiment of the scanning device which is highly insensitive to wavelength changes is further characterized in that the elements of the compensator have different Abbe numbers.

The Abbe number of an optical material is a measure of the dispersion of the material and indicates the extent of change of the refractive index of the material at a wavelength change of the beam passing through the material. The materials of the elements of the compensator now have as much as possible the same refractive index for the design wavelength so that the compensator does not have an optical strength for a beam of that wavelength. At a wavelength change, the refractive indices of the compensator elements change to a different extent so that the curved interface between these elements will act as a converging or a diverging element. Consequently, the beam exiting from the compensator acquires a small convergence or divergence with respect to the entering beam, with which convergence or divergence the variation of the optical behavior of the objective system due to said wavelength change can be compensated.

The device is further preferably characterized in that a collimator lens is arranged between the radiation source and the compensator.

25 The collimator lens, which may consist of one or more lens element(s), converts the diverging beam supplied by the source into a parallel beam. As a result, the design of the objective system will be simpler than that of an objective system which must focus a diverging beam on the information plane.

The invention also relates to an apparatus for reading and/or writing information in an information plane of an optical record carrier. This apparatus, which comprises an optical device for forming a scanning spot on the information plane, a radiation-sensitive detection system for converting radiation from the information plane into electric signals, and means for moving the scanning spot and the information plane with respect to each other, is characterized in that the optical device is a device as described

hereinbefore.

These and other aspects of the invention are apparent from and will be elucidated with reference to the embodiments described hereinafter.

In the drawings:

Fig. 1 shows a part of an embodiment of an optical apparatus for reading and/or writing an optical record carrier, provided with a scanning device;

Fig. 2 shows an embodiment of the objective system of the scanning device, and

Fig. 3 shows an embodiment of the scanning device with a temperature compensator.

Fig. 1 shows a part of a round disc-shaped optical record carrier 1 in a radial cross-section. This record carrier comprises a transparent layer 2, one side of which is provided with an information layer 3. The side of the information layer 3 remote from the transparent layer 2 may be protected from ambient influences by a protective layer 4. The side of the transparent layer 2 facing the scanning device is referred to as the entrance plane 5. The transparent layer functions as a substrate of the record carrier and forms a mechanical support for the information layer. It is alternatively possible for the transparent layer 2 to serve only as a protection for the information layer, while the mechanical support is provided by a layer on the other side of the information layer, for example by the protective layer 4 or by a further information layer and a transparent layer provided on the information layer 3. The information layer 3 of the record carrier may be provided with information in the form of optically detectable areas which are arranged in substantially parallel, concentric or spiral-shaped tracks which are not shown in Fig. 1 but are perpendicular to the plane of the drawing in the cross-section shown. The areas may have any optically detectable shape and may be, for example pits or areas whose reflection coefficient or direction of magnetization is different from that of their ambience, or a combination of these shapes.

The scanning device comprises a radiation source 6, for example a semiconductor laser emitting a diverging radiation beam 7. This beam is reflected towards a lens system by a beam splitter 8, for example a semi-transparent mirror. This system comprises a collimator lens 9 and an objective system 10 which is composed of an objective lens 12 and a planoconvex lens 13. The lenses 12 and 13 are accommodated in an objective

holder 11. The collimator lens 9 converts the diverging beam 7 into a collimated beam 14. The objective lens 12, which has an optical axis 15, converts the collimated beam 14 into a converging beam 16 which is incident on the lens 13. This lens changes the incident beam 16 into a converging beam 17 whose focus 18 is situated on the information layer 3. The
5 planoconvex lens 13 has a convex surface and a flat surface. The flat surface faces the record carrier 1 and is separated therefrom by means of a gap 19. The objective lens is shown in the Figure by means of a single lens element but may alternatively comprise a plurality of lens elements, as well as a hologram which operates in transmission or reflection. The collimator lens may also comprise a plurality of lens elements.

10 By using the collimator lens, the object, the emitting surface of the radiation source, and the image, the scanning spot 18 are conjugated at infinity and the objective system receives a parallel beam. Alternatively, the collimator lens may be omitted so that a diverging beam is incident in the objective system and a conjugation of object and image at infinity must take place. Since the objective system must then converge a diverging
15 beam, the design of this system is more difficult than in the case where a collimator lens is used.

During writing or reading information, the record carrier is rotated via a shaft 28 driven by a motor 27, by which an information track is scanned by the scanning spot 18. By moving the scanning spot and the record carrier with respect to each other in a
20 direction perpendicular to the plane of the drawing in Fig. 1, all concentric tracks, or the entire spiral track, can be scanned. The last-mentioned movement can be realized by arranging the scanning device or a part thereof, inter alia, at least the objective system, on a slide which is movable in said direction. When information is being read, the radiation of the converging beam 17 reflected by the information layer 3 is modulated with the information
25 which is stored in the successive information areas. This reflected radiation forms a reflected beam 20 which returns along the path of the on-going converging beam 14. The objective system 10 and the collimator lens 9 convert the reflected and modulated beam into a converging reflected beam 21, and the beam splitter 8 passes a part of the beam 21 to a radiation-sensitive detection system 22. The detection system receives the radiation from the
30 beam and converts it into one or more electric signals. One of these signals is an information signal 23 which represents the information read from the information plane. Another signal is a focus error signal 24 which is representative of a possible axial deviation of the focus 18 with respect to the information plane 3. This focus error signal, which can be generated in various known manners, is used as an input signal for a focus control circuit 25 which drives

an axial actuator (not shown) for the objective system in such a way that the axial position of the focus 18 coincides with the plane of the information layer 3. Another signal which is supplied by the detection system 22 is a tracking error signal which is representative of a possible deviation between the center of the scanning spot and the centerline of the
5 instantaneously read information track. This signal, which can also be generated in various known manners, is used as an input signal for a radial control circuit (not shown) which drives a radial actuator in such a way that the center of the scanning spot 18 coincides with the centerline of the track which has been read.

When information is being written in the information layer, the beam
10 from the source is modulated with the information signal to be written. This modulation can be realized with a separate modulator in the path of this beam, for example an acousto-optical modulator, which is controlled by the information signal to be written, or by direct control of the source with the information signal to be written. Also when information is being written, the detection system 22 can supply a focus error signal and a tracking error
15 signal. The information signal read from the information layer then comprises information about data which have been previously provided on the record carrier, such as addresses used for writing the actual information.

Fig. 2 shows an enlargement of the objective system and the path of the radiation through this system. The objective lens may be a planoconvex lens with an
20 aspherical surface but is preferably a lens with an aspherical convex surface 31 and an aspherical concave surface 32, as is shown in Fig. 1. The objective lens may be designed in known manner in such a way that the spherical aberrations introduced by the planoconvex lens 13 and the transparent layer 2 can be compensated thereby, so that the scanning beam
17 proximate to the focus, or scanning spot, 18 is essentially free from spherical aberration.
25 The convex surface 34 of the lens 13 is preferably also aspherical. The aberration correction can then be ensured by a plurality of lens surfaces so that a better and simpler correction is possible.

The replica process is preferably used for forming aspherical surfaces such as the surfaces 31, 32 or 34. The process starts from a glass lens element as a preform
30 and a layer of transparent synthetic material such as a curable polymer is provided in a sufficiently soft state on one or both refractive surfaces of said element. The outer surface of such a layer is given the desired shape by pressing a mold against it, whose inner surface is a negative of the desired surface. Subsequently, the synthetic material layer is cured, whereafter the lens element is released from the mold or molds. The synthetic material may

be the material manufactured under the name of Diacryl by the firm of Akzo, with the product description: Di-ethoxylated Bisphenol A Dimethacrylate and the Chemical Abstract no.: CAS no. 2448-20-2. This material can be cured with UV radiation.

Also a lens element which is completely made of a synthetic material by means of, for example, an injection molding process, may be provided with one or two aspherical surfaces in a relatively simple way. In the process of injection molding the lens element, use is made of a mold or of two molds, with the inner surface of such a mold being a negative of the desired lens surface. Known materials for these types of lenses are Polymethyl Methacrylate (PMMA) or Polycarbonate (PC). The formation of aspherical lens surfaces in synthetic material has the advantage that a cumbersome grinding and polishing process, as would be required for a glass lens element, can be dispensed with.

Lens elements having a synthetic material layer or entirely consisting of a synthetic material are, however, sensitive to temperature variations. Particularly the change of the refractive index of the synthetic material occurring at a temperature change causes a change of the optical behavior of the lens element. Moreover, the temperature change may also result in a change of the shape of the element. At the same temperature change, the change of the refractive index has a considerably greater influence on the optical behavior than a change of the shape. The variations of the optical behavior of the objective system, occurring at temperature variations and resulting in spherical aberrations, particularly occur in systems having a large numerical aperture, such as the above-described scanning device which may have an NA of 0.85.

To considerably reduce the temperature effects, a temperature compensator, as shown in Fig. 3, is arranged in the radiation path preceding the objective system. This compensator 40 consists of a first, planoconvex, lens element 41 and a second, planoconcave, lens element 42. These lens elements essentially have the same refractive index at the design temperature, for example 20°C, so that there is no refractive index difference at this temperature for the radiation beam 14 at the curved interface 43 between the first and the second element. Since the outer surfaces 44 and 45 of the compensator 40 are flat, this compensator has no optical strength at the design temperature, i.e. the parallel beam 14 entering the compensator leaves this compensator as a parallel beam 14'.

However, the refractive indices n of the materials of the elements 41 and 42 do have a different temperature dependence dn/dT . At a temperature which deviates enough from the design temperature, the refractive indices of the elements 41 and 42 will therefore be different. Then, the radiation beam 14 has a refractive index difference at the

interface 43 and since this interface is curved, it will act as a refractive lens surface. The compensator then has a small optical strength and renders the beam slightly converging or diverging, dependent on the temperature change. By choosing a suitable shape for the interface 43, the temperature dependence of the objective system 10 can be compensated by way of the temperature-dependent optical strength of the compensator 10, so that the total system 40, 10 is no longer temperature-dependent.

The material of one of the elements 41, 42 is preferably glass and that of the other element is a synthetic material. Since the refractive index of glass is substantially independent of the temperature, the choice of the synthetic material is made easier. In fact, all refractive indices of the suitable synthetic materials have a temperature dependence which is different from that of glass, so that the requirement to be imposed on the synthetic material is only that the refractive index of this material at the design temperature should be equal as much as possible to that of the glass.

In an embodiment of the scanning device according to the invention, the glass element is formed from the glass of the type number BAK4, whose refractive index is 1.566 at a wavelength of 650 nm, while the synthetic material element consists of the aforementioned material Diacryl from the firm of Akzo, and has a refractive index 1.565 at the design temperature. In this embodiment, the NA of the objective system is equal to 0.85 and the radius of curvature of the spherical interface 43 is equal to -2.925 nm. The temperature tolerances of this device are a factor of 6 better than those of a device without the temperature compensator.

If changes of the shape in the objective system, such as changes of the curvatures of the surfaces or the thickness of the lens elements, also affect the optical behavior of the objective system, these changes can be compensated by adapting the curvature of the interface 43.

The embodiment of Fig. 3 is provided with a collimator lens 9 in order that the beam 14 and, at the design temperature, also the beam 14' are parallel beams. If the objective system 10 is designed in such a way that it can focus a diverging beam to the desired scanning spot 18, the collimator lens 9 may be dispensed with.

The invention may also be used in a scanning device which has a numerical aperture of less than 0.85 and in which temperature effects occur. The objective system of such a device may consist of the objective lens 12 only which may consist of a single, for example bi-aspherical, lens element or of a plurality of lens elements.

In a scanning device in which wavelength changes may occur, as in a

device used in an apparatus with which information can be both written into and read from a record carrier, the axial position of the focus of the scanning beam may be offset with respect to the information plane due to the dispersion of the materials of the objective system, so that the scanning spot on the information plane becomes too large and crosstalk may occur between adjacent information tracks and successive information areas. To render the scanning device insensitive to wavelength changes, materials whose refractive indices at the design wavelength are equal but have a different wavelength dependence $dn/d\lambda$ may be chosen for the elements 41 and 42 of the compensator 40. Then, the compensator has no optical strength at the design wavelength, because there is no refractive index difference at the interface 43 and the outer surfaces of the compensator are flat. At a wavelength which deviates enough from the design wavelength, a refractive index difference does occur on the curved interface 43 so that this interface has a lens action. The compensator then has a small optical strength and renders the beam 14' slightly converging or diverging, dependent on the wavelength change. The wavelength dependence of the objective system can be compensated by means of the wavelength-dependent optical strength of the compensator, so that the total system 40, 10 is no longer wavelength-dependent.

The invention has been described with reference to its use in an apparatus for reading and/or writing information in an optical record carrier but it is not limited thereto. The invention may be used wherever scanning must take place at a high resolution, i.e. with a small scanning spot. Examples are scanning optical microscopes having a very high resolution or optical inspection apparatuses having a high resolving power for various uses.

CLAIMS:

1. An optical device for optically scanning an information plane, comprising a radiation source for supplying a scanning beam, and an objective system for focusing the scanning beam to a scanning spot on the information plane, characterized in that a temperature compensator comprising a cemented doublet of a planoconvex first element and
5 a planoconcave second element is arranged between the radiation source and the objective system, the convex surface of the first element being arranged against the concave surface of the second element, and the refractive indices of the first and the second element being substantially equal at the design temperature but having a different temperature dependence.
- 10 2. An optical device as claimed in claim 1, characterized in that one of the elements of the compensator consists of glass and the other element consists of a transparent synthetic material.
3. An optical device as claimed in claim 2, characterized in that said glass is
15 BAK4 and said synthetic material is Diacryl.
4. An optical device as claimed in claim 1, 2 or 3, characterized in that the objective system comprises an objective lens and a planoconvex lens, the objective lens being situated on the object side and the planoconvex lens being situated on the image side, the
20 convex surface of the planoconvex lens facing the objective lens.
5. An optical device as claimed in claim 1, 2, 3 or 4, characterized in that the elements of the compensator have different Abbe numbers.
- 25 6. An optical device as claimed in any one of claims 1-5, characterized in that a collimator lens is arranged between the radiation source and the compensator.
7. An apparatus for reading and/or writing information in an information plane of an optical record carrier and comprising an optical device for forming a scanning

spot on the information plane, a radiation-sensitive detection system for converting radiation from the information plane into electric signals, and means for moving the scanning spot and the information plane with respect to each other, characterized in that the optical device is a device as claimed in any one of the preceding claims.

1/3




FIG. 1

2/3




FIG. 2

3/3




FIG. 3

INTERNATIONAL SEARCH REPORT

International Application No

PC/EP 99/05518

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G11B7/135

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G11B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 638 221 A (IWAKI MAKOTO ET AL) 10 June 1997 (1997-06-10) abstract column 1, line 57 -column 2, line 3 column 2, line 44 -column 3, line 11 column 6, line 33 -column 11, line 35; figures 3-11	1,2,5,7
X	US 4 721 373 A (SUGIYAMA TAKAHIRO) 26 January 1988 (1988-01-26) abstract; figures 1-10 column 1, line 36 - line 55 column 2, line 21 -column 4, line 52 -/--	1,5,7

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

1 November 1999

Date of mailing of the international search report

09/11/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Pariset, N

INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 99/05518

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 753 524 A (SUGIYAMA TAKAHIRO) 28 June 1988 (1988-06-28) cited in the application abstract; figures 1-16 column 1, line 30 - line 58 column 2, line 35 -column 4, line 47 -----	1,5,7
A	PATENT ABSTRACTS OF JAPAN vol. 1997, no. 12, 25 December 1997 (1997-12-25) -& JP 09 204678 A (SANKYO SEIKI MFG CO LTD), 5 August 1997 (1997-08-05) abstract -----	1-7
A	US 4 632 520 A (YAMAKAWA HIROMITSU) 30 December 1986 (1986-12-30) abstract; figures 1-8C column 1, line 56 -column 3, line 6 column 4, line 4 -column 6, line 64 -----	1-7
A	US 4 815 059 A (NAKAYAMA MASAHIKO ET AL) 21 March 1989 (1989-03-21) abstract; figures 6-12 column 7, line 22 -column 13, line 42 -----	1-7
A	EP 0 727 777 A (SONY CORP) 21 August 1996 (1996-08-21) cited in the application the whole document -----	1-7

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 99/05518

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5638221	A	10-06-1997	US 5479296 A	26-12-1995
			US 5321550 A	14-06-1994
			DE 4003962 A	16-08-1990
			FR 2642883 A	10-08-1990
			GB 2232291 A,B	05-12-1995
			US 5657171 A	12-08-1997
			US 5644437 A	01-07-1997
			US 5657168 A	12-08-1997
			DE 4006275 A	13-09-1990
			FR 2643727 A	31-08-1990
			GB 2229292 A,B	19-09-1990
			JP 3155514 A	03-07-1991
			JP 2902435 B	07-06-1999
			US 5173809 A	22-12-1992
			US 5491587 A	13-02-1996
US 4721373	A	26-01-1988	JP 1479492 C	10-02-1989
			JP 62119512 A	30-05-1987
			JP 63027685 B	03-06-1988
US 4753524	A	28-06-1988	JP 1593622 C	14-12-1990
			JP 2017086 B	19-04-1990
			JP 61275808 A	05-12-1986
JP 09204678	A	05-08-1997	NONE	
US 4632520	A	30-12-1986	JP 59211013 A	29-11-1984
US 4815059	A	21-03-1989	JP 1950000 C	10-07-1995
			JP 6085233 B	26-10-1994
			JP 63007530 A	13-01-1988
EP 0727777	A	21-08-1996	JP 8221790 A	30-08-1996
			CN 1135075 A	06-11-1996
			SG 45208 A	16-01-1998
			US 5774281 A	30-06-1998
			US 5786947 A	28-07-1998

